

Clay, dry construction plate according to LP (type A) - TM 07 – MHK I – 0,6 - 25

Clay dry construction plate for paneling and sheathing

For montage to ceiling, wall or slant



Properties

Lehm-dry construction plate with double-sided glass fibre -mesh for laying on compensation areas (areas without heating medium) at systems RIVIERA and TOSKANA. Suitable for paneling of stands or sheathing of wooden areas or masonries for example, or. Can be fixed to walls, ceilings or slants. As dry-plastering plate for ArgillaTherm clay upper plaster no. 1-2.

Composition

clay, sands, hamp fibres, hamp flakes, glass fibre mesh 12mm.

Characteristics

dimension	750 x 750 x 25 mm
Dimensioning tolerance	MHK I ($\pm 1,0$ mm)
weight plate / m ²	8,70 kg / 15,50 kg
Bulk density	Bulk density class 0,7 (620 kg/m ³)
Surface reinforcement	12mm glass fibre-mesh (both-sided)
Biegezugfestigkeit longitudinal/transverse	3,65 / 2,15 N/mm ²
Surface strength	0,11 N/mm ²
Water vapor diffusion resistancy	mind. $\mu = 5/10$
Thermal conductivity	0,17 W/mK
Specific heat storage capacity	1,5 kJ/kgK
Fire classification	A 2
Water vapor absorption class	WS III

Forms of delivery

package	Range of coverage	Article no.
1 palette à 60 plates 750 x 750mm 60 plates 750 x 375mm	50,62 m ²	ZLBP757525

Dimensions incl. palette approx. 120 x 80 x 170 cm (L x W x H) with edge protection and cardboard cover.

weight incl. palette approx. 815 kg.

Storage

Unlimited at dry storage.

Application

The clay compensation plate can be used in the complete interior works field at walls, ceilings and slants as compensation plate (on areas without heating medium) in conjunction with the heating systems RIVIERA and TOSKANA.

Handling

Machining of the plates

Cutting of plates by means of all popular woodworking and stoneworking machines, such as jigsaw, circular saw and holesaw. Attention: increased dust appearance! Pay attention to the appropriate health and safety rules!

Alternatively plates can be broken across an edge. For that purpose one-sided cut the scrim by means of a cutting knife, break the plate and then cut the scrim at the other side. Finish the broken edges by means of a rasp or mason's plane, if necessary.

Montage

At montage to continuous wooden plates the butt joints should not be above the butt joints of the carrier board.

For fixing use stainless-steel load distributors- Art.-No55100 and suitable stainless-steel-screws.

System products

ArgillaTherm clay upper plaster no. 1-2

Machine usable clay plaster ready-mix acc. DIN 18947.

ArgillaTherm clay paint no. 3-1

Sprayable and brushable clay paint as ready-mix.

 **ArgillaTherm**[®]
GmbH

Working conditions for construction and application areas of our products are very various. In our technical data sheets, we can only provide basic processing guidelines. These comply with our current state of knowledge. Planners and processors are obligated to examine suitability and potential applications for the intended use. For application scenarios that are not expressly mentioned in our data sheets, planners and processors are obligated to refer to the ArgillaTherm[®] application technology. If the processor uses the product beyond the area of application in the instruction manual, without previous consultation of the ArgillaTherm[®] application technology, they are completely liable for the potential resulting damages. All herein contained descriptions, sketches, photographs, data, conditions, weights etc. can be changed without prior notice and do not represent contractual agreements of the of the products characteristics.

Possible property rights as well as existing laws and regulations are to be considered by the recipient of our product under their own responsibility. The reference of brand names of other companies does not act as a recommendation and does not rule out the use of other similar products, if they have not been classified for application with our products in the system. Our information solely describes characteristics and benefits of our product and does not provide a guarantee. A guarantee for specific properties or the suitability of the product for a certain purpose cannot be derived from our information. We only assume liability for incomplete or incorrect statements within our informational material in case of gross culpability (intent or severe negligence); possible demands of the product liability law remain unaffected.